

**Waiver:**

This data sheet is for guidance only and must not be used for proper working drawings. Please contact Stannah Lifts for particular details before proceeding. Owing to our policy of continual improvement we reserve the right to alter specifications and dimensions without prior notice.

# SYSTEM 21



## Machine Room-Less

### Machine Room Cabinet

MRC

10 Person (800kg)

Travel: 12.8m max.  
Speed: 0.5m/s max.



**Option: MRC-RM**  
Machine Room in Cabinet  
- Recess Mounted

Not available on the guide side

\*\* Well Width (W)  $+25$   
 $-0$

\*\* Well Depth (D)  $+25$   
 $-0$

An area of 810 wide x 725 deep, and a clear height of 2125mm should be available in front of the machinery cabinet for

A MACHINERY CABINET supplied with the lift, is fitted in the shaft wall. A structural clear opening in front of the fire barrier is to have minimum dimensions of 850 wide x 400 deep x 2125 high. Further details may be found on builders work drawings.

† Note: Controller not fire certified. Fireproof barrier behind cabinet to be provided by builder.

Part 'M' Bldg Regs: A clear landing 1500mm wide x 1500mm deep in front of lift doors should be provided for access by wheelchair users.

**Option: MRC-SM**  
Machine Room in Cabinet  
- Surface Mounted

\*\* Well Width (W)  $+25$   
 $-0$

\*\* Well Depth (D)  $+25$   
 $-0$

An area of 810 wide x 725 deep, and a clear height of 2125mm should be available in front of the machinery cabinet for maintenance.

A MACHINERY CABINET, supplied with the lift, can be positioned on any side adjacent to, or remotely within 8m of the lift well. The external dimensions of the cabinet are 810 wide x 365 deep and 2100 high. Further details may be found on builders work drawings.

Part 'M' Bldg Regs: A clear landing 1500mm wide x 1500mm deep in front of lift doors should be provided for access by wheelchair users.

\*\* See datasheet 10-1 for information on well dimensions, imposed loads and general details of 10 person lifts.